











Characteristics

When we set out with the firm intention of producing the best equipment in the market, we had the advantage enjoyed by every new company: there were no technical limits imposed by an existing range of models!

This unit has been designed for use with insecticides, acaricides and fungicides (mostly wettable powders) which are soluble in oil or water. Light in weight for convenient use in areas where poor road and tracks make it difficult to handle heavy equipment. The only mass produced unit with air intake valve covered, providing a silencer effect and protection against dust and solution particles.

- · Petrol Tank made from stainless steel
- · Fog Tube made from stainless steel
- · Formulation Tank made from stainless steel
- · Cooling Jacket made from enamelling sheet

All other parts getting in contact with the chemicals are made from brass, viton or teflon.

Emergency cut-off device for solution available upon request.

Technical Specifications

Weight in kg, empty but ready for use	7.9kg
Dimensions L x W x H in cm	137.5 x 27 x34
Solution Tank capacity in l	5.7* or 10
Fuel consumption, approx. in l/h	2.0
Performance of combustion chamber in KW/HP	18.7/25.4
Maximum flow rate, approx. In l/h	42
Effective horizontal reach, indoors appro	ox. in m
water based with carrier i.e. X - 10 oil based	40 >100
Power Supply	4 x 1.5 V LR20
(flashlight batteries)	(LR6 option)

*standard

Considering the maximum flow rate, an operator can treat at a flow rate of 1 litre/2.500 m³ up to 105.000 m3/h or 3.708.000 ft3/h


Special Executions

• Dual-purpose cone shaped fog tube for both oil and water based fogging (Patented)



• Emergency cut-off device (optional)





No. 32 Ang Mo Kio Industrial Park 2 #01-01/02 Sing Industrial Complex Singapore 569510 Tel: (65) 6482 1828 Fax: (65) 6481 2631

Email: agro@agrotech.com.sg Website: www.agrofog.com

Agrofog Sdn. Bhd

Malaysia Office:

agrofog° =

No. 18 Jalan PJS 11/14 Bandar Sunway Industrial Park 47500 Subang Jaya Selangor Malaysia Tel: 03-5638 8486 Fax: 03-5638 8491

Penang: 04-6411734

Email: agro@agrofog.com.my Website: www.agrofog.com