



## Technical Specifications

<b>Weight in kg, approx.</b>	196
<b>Dimensions LxWxH in cm</b>	110 x 95 x 68
<b>Engine</b>	18 hp, 4 cycles
<b>Drive</b>	2 V-belts
<b>Side channel blower</b>	
<b>Discharge rate (m<sup>3</sup>/min)</b>	6.0 at 3500 rpm
<b>Pressure (bar)</b>	0.25 (0.3 max)
<b>Remote control system</b>	Electric starter for engine solenoid valve and application of chemical solution
<b>Fuel tank capacity in l</b>	20
<b>Fuel consumption, l/h</b>	4,5
<b>Formulation tank in l, made from stainless steel</b>	75
<b>Battery</b>	12 Volts DC, 45 Ah
<b>Nominal output in l/h</b>	40 [water or oil]
<b>Output in l/h</b>	60 [water, max]
<b>Air filter</b>	Paper star filter
<b>Number of aerosol nozzles</b>	4

## Optionals

- hose extension, 10 m long with aerosol nozzle, output 10 l/h
- accessory kit for treatment of city sewerage through man-holes
- trolley
- solution tank (50 l) made from stainless steel
- additional fuel tank 20 l
- agitator



**Also available with electric motor, 11 KW, 3-phase main supply IGEBA U 40 HD-E and for automatic operation.**

## Why Ultra Low Volume application ?

The aim is to keep the application rate as low as possible and thereby diminish both the cost of the total quantity applied as well as the actual treatment time.

The chemical preparation is conducted to the spray heads where a powerful blast of air from a blower breaks up the chemical substance into minute droplets. On its way to the spray head, the pesticide passes through a flow meter or dosage nozzles to ensure a constant application rate and produce droplets of uniform size. This shortens the treatment time and reduces the quantity of active agent applied, thereby achieving the highest standards of efficiency and optimum coverage.

## Benefits

**This application technique is exceptionally safe!**  
**The aerosol generator operates very efficiently!**

Operating direction is variable right through 360°. Moreover, every nozzle can be operated individually.

## The aerosol generator is very reliable!

A special design, in conjunction with highly effective protective measures, ensures dependable application also under the stringent conditions of public hygiene. Incidentally, cold aerosols are virtually invisible.

## Droplet size data for IGEBA ULV Aerosol-Generators

Ambient temperature: 22.0°C  
Formulation temperature: 22.0°C

per nozzle	'D(v,0.5)'	'D(v,0.9)'
water	13.4 µm	30.4 µm
oil	< 12 µm	< 20 µm

## Space treatment

IGEBA ULV Aerosol-Generators produce aerosol droplets, using highly concentrated formulations. The rate of application depends upon active ingredient and formulation used but usually ranges from 0,5 - 4 l/ha. If mounted on a vehicle the forward speed of the vehicle should not exceed 10 km/h. EC (emulsion concentrates) and ULV formulations can be diluted with diesel or kerosene or water, while WP (Wettable powders) can be diluted with water.

### Regional Office:



**Agro Technic Pte Ltd**  
No. 32 Ang Mo Kio Industrial Park 2 #01-01/02  
Sing Industrial Complex Singapore 569510  
Tel: (65) 6482 1828 Fax: (65) 6481 2631  
Email: [agro@agrotech.com.sg](mailto:agro@agrotech.com.sg) Website: [www.agrofog.com](http://www.agrofog.com)

### Malaysia Office:



**Agrofog Sdn. Bhd**  
No. 18 Jalan PJS 11/14 Bandar Sunway Industrial Park  
46150 Subang Jaya Selangor Malaysia  
Tel: 03-56388486 Fax: 03-56388491  
Email: [agro@agrofog.com.my](mailto:agro@agrofog.com.my) Website: [www.agrofog.com](http://www.agrofog.com)